



地址：浙江省宁波市会展路 181 号 Add: No.181,HuiZhan Road ,Ningbo city, China 315000

电话：(Tel)86-574-87990349， 传真 (Fax) :86-574-88193499 邮编 (P.C) :315000

http://www.rubbersealing.com E-mail: sales@rubbersealing.com , MSN: towerpacking@hotmail.com



Ceramic raschig ring

Ceramic Raschig Ring is the first development of a random packing. Ceramic Raschig ring shape is simple, its height and diameter equal size..

The **Ceramic raschig ring** is common regular packing that they are still used for refilling existing columns and other applications. Its surface ratio is higher than ceramic cylinders and balls by 30% and its ring shape has high mechanical stability.

Specifications for Ceramic Raschig ring

Size IN	Packing Size mm	Dimensions (ODxHxTHK) mm	Surface Area m ² /m ³	Void %	Bulk Quantity pcs/m ³	Bulk Density kg/m ³	F Factor (dry) m ⁻¹
	6	6x6x2	789	73	3110000	737	2030
	10	10x10x2	440	70	720000	700	1280
1/2"	15	15x15x2	330	70	237000	590	960
	16	16x16x2	305	73	192500	730	784
1"	25	25x25x2.5	190	78	49000	505	400
1.1/2"	40	40x40x5	126	75	12700	577	305
2"	50	50x50x5	93	81	6000	457	177
3"	80	80x80x9.5	90	68	1910	714	234
4"	100	100x100x10	70	70	1000	700	172
6"	150	150x150x15	50	68	295	790	142