



地址：浙江省宁波市会展路 181 号 Add: No.181,HuiZhan Road ,Ningbo city, China 315000

电话：(Tel)86-574-87990349， 传真 ( Fax ) :86-574-88193499 邮编 ( P.C ) :315000

http://www.rubbersealing.com E-mail: [sales@rubbersealing.com](mailto:sales@rubbersealing.com) , MSN: [towerpacking@hotmail.com](mailto:towerpacking@hotmail.com)



## Metal Intalox Saddle Ring

The shape of Intalox saddle is between ring and saddle, and therefore having advantages of the two. This structure helps distribution of the liquid and increases gas channels. It has smaller resistance, larger flow rate, higher efficiency, better filling intensity and rigidity than PALL ring. It's a kind of bulky filling used most widely at present.

Model	Size d×h×δ mm	Number n/m <sup>3</sup>	Cumulate Weight (γP) kg/m <sup>3</sup>	Specific Surface Area α m <sup>2</sup> /m <sup>3</sup>	Voidage (ε) m <sup>3</sup> /m <sup>3</sup>	Dry Filling Factor (α/ε <sup>3</sup> ) m <sup>-1</sup>
DG25	25×20×0.5	119047	353	185	0.96	209.1
DG38	38×24×0.5	31654	249.6	140.4	0.968	126.6
DG50	50×28×0.8	11160	239.7	90.1	0.97	84.7
DG76	76×48×1	3320	244.7	57.6	0.97	63.1