



地址: 浙江省宁波市会展路 181 号 Add: No.181,HuiZhan Road ,Ningbo city, China 315000
电话: (Tel)86-574-87990349, 传真 (Fax) :86-574-88193499 邮编 (P.C) :315000
<http://www.tcipacking.com> <http://www.rubbersealing.com> E-mail: sales@tcipacking.com

PTFE filament packing with PTFE impregnated



Description:

Braided from PTFE filament and impregnated with PTFE dispersion. It has the better internal structure, higher cross-sectional density and structural strength than traditional PTFE packing.

Application areas:

Multipurpose packing widely used in piston pumps, mixing agitator, the reaction to push, industrial and chemical industries with the valves.

Application media:

For a variety of media, including corrosive medium: hot and cold water, steam, solvents, oil, grease, dilute acids and alkalis, salt water, sewage and so on.

Advantages:

Suitable for a very wide range of applications, reduce maintenance time and cater for very demanding duties.

Technical Data sheet:

| Technical data | Rotating | Reciprocating | Valves |
|----------------|---------------|---------------|--------|
| Pressure | 2 Mpa | 15 Mpa | 20 Mpa |
| Shaft speed | 10 m/s rotary | | |
| Temperature | -200℃to +280℃ | | |
| PH range | 0~14 | | |