



地址: 浙江省宁波市会展路 181 号 Add: No.181,HuiZhan Road ,Ningbo city, China 315000
 电话: (Tel)86-574-87238791, 传真 (Fax) :86-574-87238794 邮编 (P.C) :315000
 http://:www.rubbersealing.com E-mail: sales@rubbersealing.com , MSN: towerpacking@hotmail.com



T.C.I SUPPER SADDLE RING IS a versatile and economical industry standard with well-known performance characteristics. Low pressure drop, high flux , high efficiency , easy to handle.

Applications of super saddle ring:

- Absorption, scrubbing, and stripping services
- Pulp and paper service, such as bleach plant absorbers
- Versatile alternative to ceramic saddles

Performance of super saddle ring:

1. Good Capacity and Low Pressure Drop

- Higher capacity and lower pressure drop than ceramic saddles.
- Multiple sizes provide ability to optimize capacity and efficiency based on application requirements.

2. Higher Liquid Hold-up and Residence Time

- Relatively high liquid hold-up allows good absorption efficiency with slow chemical reaction.

3. Versatile Standard Packing

- Lower sensitivity to liquid and vapor distribution quality allows use with conventional liquid distributors.

Size		OD *H * T mm	Quantity n /m ³	Bulk Density kg/m ³	specific surface area m ² /m ³	void rate ε %	dry packing factor m- 1
1.5"	38mm	38*19*1.2	57200	160	207	0.90	108
2"	50mm	50*25*1.5	6710	117	108	0.93	69
3"	76mm	76*38*2	1480	94	89	0.94	52

* Data sheet for Super saddle ring