



地址：浙江省宁波市会展路 181 号 Add: No.181,HuiZhan Road ,Ningbo city, China 315000

电话：(Tel)86-574-87990349， 传真 (Fax) :86-574-88193499 邮编 (P.C) :315000

http://www.rubbersealing.com E-mail: sales@rubbersealing.com , MSN: towerpacking@hotmail.com



METAL PALL RING

Metal Pall ring is one of the most common and well known random tower packings, it is an industry standard design media developed from the Raschig Ring and is used widely in variety of applications. By improving the Metal pall ring geometry enables high gas and liquid transfer rates, greater capacity and lower pressure drop than standard cylindrical rings. The interior and exterior contacting surfaces of the Metal pall ring provide for an effective distribution of liquids and gasses and resist plugging, fouling and nesting.

Advantages: 1), Lower pressure drop. 2), Huge flux. 3), High efficiency.

Material available: Carbon steel, stainless steel including 304, 304L, 410, 316, 316L.

Sizes (mm)	Bulk density (kg/m ³)	Number (per m ³)	Surface area (m ² /m ³)	Free volume (%)
16*16*0.3	360	201000	346	95.5
25*25*0.4	302	5100	212	96.2
25*25*0.5	400	51000	216	95
25*25*0.6	461	51000	219	94.2
38*38*0.4	218	15000	143	97.2
38*38*0.5	262	15180	145	96.7
38*38*0.6	328	15000	146	95.9
50*50*0.5	194	6500	106	97.5
50*50*0.7	285	6500	108	96.4
50*50*0.9	365	6500	109	95.4
76*76*0.8	205	1830	69	97.4
90*90*1.0	229	1160	62	97.1